



Evolution Fasteners (UK) Ltd
 Units 2A & 2B Clyde Gateway Trade Park
 Dalmarnock Road, Rutherglen, Glasgow G73 1AN
 Tel: +44 (0)141 647 7100 / Fax: +44 (0)141 647 5100
 Email: technical@evolutionfasteners.co.uk



www.evolutionfasteners.co.uk



PRODUCT DATASHEET

A4 BI-METAL TEK SCREW

Product Details

Designed for: *Fastening in aluminium/steel sheeting and panels*
 Head style: *Hexagonal*
 Drive bit: *5/16" hexagonal*
 Thread form: *Twin, coarse thread (Tek 3)/fine thread (Tek 5)*
 Material grade: *A4 stainless*
 Coating: *Electroplated zinc*
 Recommended drill speed: *1500 – 2500 RPM*

Tek 3 range – for light steel

Product Code	Size	Drill point	Effective thread length	Drilling Capacity	Washer	Steel thickness
A4BM25-3	5.5 x 25mm	Tek 3	14.0mm	1.2 - 4.0mm	16mm	1.2 - 4.0mm
A4BM38-3	5.5 x 38mm	Tek 3	27.0mm	1.2 - 4.0mm	16mm	1.2 - 4.0mm
A4BM50-3	5.5 x 50mm	Tek 3	38.0mm	1.2 - 4.0mm	16mm	1.2 - 4.0mm
A4BM75-3	5.5 x 75mm	Tek 3	60.0mm	1.2 - 4.0mm	16mm	1.2 - 4.0mm

Tek 5 range – for heavy steel

Product Code	Size	Drill point	Effective thread length	Drilling Capacity	Washer	Steel thickness
A4BM38-5	5.5 x 38mm	Tek 5	15.0mm	4.0 – 12.5mm	16mm	4.0 – 12.5mm
A4BM50-5	5.5 x 50mm	Tek 5	30.0mm	4.0 – 12.5mm	16mm	4.0 – 12.5mm

Technical Data

Hardness Rating (Vickers scale)		
Diameter	Surface Hardness	Core Hardness
5.5mm	385.9HV0.3	309.7HV0.3

Ultimate Mechanical Performance		
Diameter	Tensile Strength	Shear Strength
5.5mm	13.2kN	10.9kN

NOTE: The results expressed in the datasheet are taken as mean loads from a range of empirical tests and are ultimate unfactored loads. Each specifier or end user should make his/ her own decision on what safety factors to use relevant to their design application (such as BS 5950, EN 1991, etc).

Errors and Omissions Excepted.

Copyright © 2017 Evolution Fasteners (UK) Ltd. All rights reserved.



Technical Data continued...

Tek 3 range – Unfactored pull out values							
Diameter	Drill Point	Steel Thickness					
		1.2mm	1.6mm	2.0mm	2.5mm	3.0mm	4.0mm
5.5mm	Tek 3	1.8kN	2.2kN	2.5kN	3.4kN	4.3kN	6.2kN

Tek 5 range – Unfactored pull out values							
Diameter	Drill Point	Steel Thickness					
		4.0mm	5.0mm	6.0mm	8.0mm	10.0mm	12.5mm
5.5mm	Tek 5	6.8kN	7.4kN	8.2kN	9.7kN	10.4kN	11.9kN